



Description

Tinted Hydrophilic polyurethane film with Poly/Cotton scrim embedded. Coated with adhesive and a paper release liner. Suitable for use in skin contact applications.

Characteristics

- Medium moisture vapor transmission rate
- Pigmented film
- Thickness between 0.5—10 mils

Properties

Tests Performed		Typical Values
Peel Force From Liner	(g/2 inch)	66
Total Weight	(g/m ²)	35
Peel From Stainless Steel @180° (g/2 inch)		1078
Typical values are intended to used as a guide and are not intended		

Typical values are intended to used as a guide and are not intended for specification purposes



Poly/Cotton scrim Tinted TPU Acrylic Adhesive Si Liner

Ordering Information

Width Maximum 61 inches

Diameter Maximum 20 inches

Length Maximum 6,000 feet

Storage Temperature 50-80°F; Humidity 40-60%

Limited Warranty and Conditions—Please Read Carefully

Mylan believes the information in this publication is an accurate description of the typical characteristics and/or uses of the product(s). It is the purchaser's responsibility to thoroughly test the product in the purchaser's specific application to determine its performance, efficacy and safety, especially in light of any third party intellectual property rights. Suggestions of uses should not be taken as inducements to infringe any particular patent or other protected proprietary rights.

Unless Mylan provides you with separate specific written warranty of fitness for a particular use, Mylan's sole warranty is that the product(s) as supplied will meet Mylan's then current sales specification. MYLAN SPECIFICALLY DISCLAIMS ANY OTHER EXPRESS OR IMPLIED WARRANTY, INCLUDING THE WARRANTIES OF MERCHANTABILITY AND OF FITNESS FOR USE. Your exclusive remedy and Mylan's sole liability for breach of warranty is limited to refund of the purchase price or replacement of any Mylan product shown to be other than as warranted at Mylan's option, and Mylan expressly disclaims any liability for incidental or consequential damages.

Applicable test methods and product specifications are available upon request.

Mylan believes the information in this publication is an accurate description of the typical; characteristics and/or uses of the product(s). It is the